

# Linear: 24 INCH

LED Module for Linear Applications

**Module No. L24GAZ48S3580C**

<b>No. of LED</b>	48 LEDs
<b>Size</b>	24 IN
<b>Material</b>	MCPCB
<b>Color Temperatures Available</b>	2700K - 5000K
<b>CRI</b>	80/90
<b>Dimmable</b>	YES
<b>Type</b>	CONSTANT CURRENT
<b>UL Class</b>	CLASS 2
<b>Compliance</b>	ROHS , DLC

## Driver

<b>Input Voltage Range</b>	36 V
<b>Input Current Range</b>	0 - 1200 mA

## Current

<b>Typ. Current on Board</b>	130 mA 260 mA 520 mA
<b>Abs Max Current on Board</b>	1200 mA

## Voltage

<b>Typ. Voltage on Board</b>	32.46 V 34.20 V 35.13 V
------------------------------	-------------------------------

## Applications

- ARCHITECTURAL LIGHTING
- LINEAR LIGHTING
- GENERAL LIGHTING
- CUSTOM / RETROFIT



## Features

- LED CHIP PACKAGE 2835
- 3 STEP MACADAM BINNING
- UL-RECOGNIZED COMPONENTS
- IN-STOCK SHIP TIME 24-48 HOURS
- PERFORMANCE PARAMETERS FOR 3500K, 80 CRI

## Connection Spec

<b>Input Wire</b>	SOLID/FINE STRANDED WIRE
<b>Cross-Section</b>	24-18 AWG 0.2 - 0.7 MM2
<b>Input Wire Strip Length</b>	7 - 8 MM

Call: 805.499.9513 | Email: [sales@wcico.com](mailto:sales@wcico.com)  
World Class Illumination | [www.wcico.com](http://www.wcico.com)